



**SPECIFICATIONS -PRO SERIES DECKOVER
PRO SERIES DECKOVER GN 25.9K**

	8.5 x 25	8.5 x 27	8.5 x 30	8.5 x 32	8.5 x 35	8.5 x 40
Model #	ST- PSD010225- 259G	ST- PSD010227- 259G	ST- PSD010230- 259G	ST- PSD010232- 259G	ST-PSD010235-259G	ST-PSD010240-259G
CAPACITIES						
GVWR (lbs)	25900					
GAWR (lbs/axle)	12000					
Curb Weight	6100	6820	6380	6640	8360	9300
Payload	19800	19080	19520	19260	17540	16600
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck			2-5/16" Adjustable Gooseneck		
Tongue	Fabricated Single Piece Gooseneck					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Frame	12", 14 lb/ft I-Beam, Low Profile Pierced Beam Frame, Undercarriage Cross Bracing			12", 19 lb/ft I-Beam, Bridge Under Frame, Low Profile Pierced Beam Frame, Undercarriage Cross Bracing		12", 26 lb/ft I-Beam, Bridge Under Frame, Low Profile Pierced Beam Frame, Undercarriage Cross Bracing
Crossmembers	3" Steel Channel, 16" On-Center					
Beavertail	5' Cleated					
Ramp(s)	Double Spring Assist, Dual Fold-Over, Full Width					
Integrated Step(s)	Drop Down Side Step (1 on each side)					
Axle	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension					
Hubs	Oil Bath					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST235/80R16E 10-PLY					
Wheels	16" Dual, 8-Lug Steel					
Tie Downs	(8) 3/4" D-Rings, Stake Pockets, Chain Spools, and Rub Rail					
Exterior Lights	(2) LED Swivel Loading Light (2,000 Lumens), Full LED, DOT Compliant, Mid Ship Turn Signals					
Bulkhead	HD Tube			HD Tube		
Mud Flaps	Large, 20"W x 24"L					
Decking	2" Pressure Treated Pine, Steel Tread Plate Over Wheels					
Exterior Storage	Integrated Gooseneck Toolbox, Spare Tire Carrier, Tool Tray and Winch Receiver Tube (In Neck)					
Coupler Height	31-39.75		31-39.75		31-39.75	
Deck Height	32		32		32	
Length Ramp	60		60		60	
DIMENSIONS						
Overall Length	414		474		534	594
Deck Height	32		32		32	
Coupler Height	31-39.75		31-39.75		31-39.75	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -PRO SERIES DECKOVER
PRO SERIES DECKOVER GN 25K**

	8.5 x 25	8.5 x 27	8.5 x 30	8.5 x 32	8.5 x 35	8.5 x 40
Model #	ST-PSD010225-250G	ST-PSD010227-250G	ST-PSD010230-250G	ST-PSD010232-250G	ST-PSD010235-250G	ST-PSD010240-250G
CAPACITIES						
GVWR (lbs)	25000					
GAWR (lbs/axle)	10000					
Curb Weight	5800	6010	6280	6640	8570	9300
Payload	19200	18990	18720	18360	16430	15700
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Fabricated Single Piece Gooseneck					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Frame	12", 14 lb/ft I-Beam, Low Profile Pierced Beam Frame, Side Rails - 6" Steel Channel, Undercarriage Cross Bracing			12", 19 lb/ft I-Beam, Bridge Under Frame, Low Profile Pierced Beam Frame, Side Rails - 6" Steel Channel, Undercarriage Cross Bracing		
Crossmembers	3" Steel Channel, 16" On-Center					
Beavertail	5' Cleated					
Ramp(s)	Full Width EZ-Lift Ramps					
Integrated Step(s)	Drop Down Side Step (1 on each side)					
Axle	(2) 10000 lb. Slipper Spring Brake, Hutch Spring Suspension					
Hubs	Oil Bath					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST235/80R16E 10-PLY					
Wheels	16" Dual, 8-Lug Steel					
Tie Downs	(8) 3/4" D-Rings, Stake Pockets, Chain Spools, and Rub Rail					
Exterior Lights	(2) LED Swivel Loading Light (2,000 Lumens), Full LED, DOT Compliant, Mid Ship Turn Signals					
Mud Flaps	Large, 20"W x 24"L					
Decking	2" Pressure Treated Pine, Steel Tread Plate Over Wheels					
Exterior Storage	Integrated Gooseneck Toolbox, Spare Tire Carrier, Recessed In Neck, Tool Tray and Winch Receiver Tube (In Neck)					
Deck Height	33.5		33.5		33.5	
Length Ramp	60		60		60	
DIMENSIONS						
Overall Length	408		468		528	594
Deck Height	33.5		33.5		33.5	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -PRO SERIES DECKOVER
PRO SERIES DECKOVER GN 32K**

	8.5 x 25	8.5 x 27	8.5 x 30	8.5 x 32	8.5 x 35	8.5 x 40
Model #	ST-PSD010225-320G	ST-PSD010227-320G	ST-PSD010230-320G	ST-PSD010232-320G	ST-PSD010235-320G	ST-PSD010240-320G
CAPACITIES						
GVWR (lbs)	32000					
GAWR (lbs/axle)	16000					
Curb Weight	6470				9220	9500
Payload	25530				22780	22500
CHASSIS						
Coupler	3" Square Gooseneck					
Tongue	Fabricated Single Piece Gooseneck					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Frame	12", 19 lb/ft I-Beam, Low Profile Pierced Beam Frame				12", 19 lb/ft I-Beam, Low Profile Pierced Beam Frame	
Crossmembers	3" Steel Channel, 12" On-Center					
Beavertail	5' Cleated					
Ramp(s)	Double Spring Assist, Dual Fold-Over, Full Width					
Integrated Step(s)	Drop Down Side Step (1 on each side)					
Axle	(2) 15000 lb. Slipper Spring Brake, Hutch Spring Suspension	Hutch Spring Suspension			(2) 15000 lb. Slipper Spring Brake, Hutch Spring Suspension	
Hubs	Oil Bath				Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish				Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY				215/75R17.5J 18-PLY	
Wheels	17.5", 8 on 275mm Steel				17.5", 8 on 275mm Steel	
Tie Downs	(8) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail				(8) 5/8" D-Rings, Stake Pockets, Chain Spools, and Rub Rail	
Exterior Lights	Full LED, DOT Compliant				Full LED, DOT Compliant	
Bulkhead	HD Tube				HD Tube	
Decking	2" Pressure Treated Pine, Steel Tread Plate Over Wheels				2" Pressure Treated Pine, Steel Tread Plate Over Wheels	
Exterior Storage	Integrated Gooseneck Toolbox, Spare Tire Carrier, Tool Tray and Winch Receiver Tube (In Neck)				Integrated Gooseneck Toolbox, Spare Tire Carrier, Tool Tray and Winch Receiver Tube (In Neck)	
Coupler Height					31-39.75	
Deck Height	33.5				32	33.5
Length Ramp	60				60	
DIMENSIONS						
Overall Length	408	432	468		534	594
Deck Height	33.5				32	33.5
Coupler Height					31-39.75	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.